USAF_Declass/Release Instructions On File 25X1C4a 3 JUNE 1974 STANDARD OPERATING PROCEDURE NUMBER 50-3105-3 WEATHER MINIMA To establish weather minima and reporting 25X1A2g procedures for the 2. SCOPE: This SOP applies to aircrews flying in the and AWS. 25X1A2g 3. MINIMA: VFR Minimums: The minimums for VFR flights in the 25X1A2q are 1,500 foot ceiling and 3 mile visibility. Helicopter flights will be conducted in accordance with the minimums described in AFM 60-16. Special VFR Minimums: The minimums for Special VFR operations in the Control Zone are 1,000 foot ceiling and 2 mile visibility. Aircrews must request Special VFR flights before the Control Tower can approve. The minimums for IFR flights in the IFR Minimums: 25X1A2g are 600 foot ceiling and 1 mile visibility. will be considered to be 25X1A2g below landing/takeoff minimums when the ceiling is less than IFR minima. PROCEDURES: The Duty Forecaster will notify the Control Tower and Operations Officer whenever weather conditions are observed or forecast to be below the VFR minima during periods The Control Tower will 25X1A2a of flying in the relay this information to all aircraft flying in the ■ When AWS manning permits, runway visibility 25X1A2g observations will be made; otherwise, prevailing visibility will be used. REGISTRY DISTRIBUTION OFFICE IMFO | OFFICE | ACT INFO P/SA SUPERSEDES: SOP 50-3105-3, 1 MAY PD EXO BFD OPR: Operations D/OPS D/M SAS CMD DISTRIBUTION: A & B IDEA EMO WX FILE INTEL DET-D CC DET-G COMMO DET-H SS BANJO Approved For Release 2001/08/27 : CIA-RDP33-02415A000600070007-0

Approved For Release 2002/508/1279aCIA-RDP33-02415A000600070007-0



25X1A9a

APPROVED:



SUPERSEDES: SOP 50-3105-3, 1 MAY 70

ATTACHMENT 1

INSTRUMENT APPROACH MINIMUMS

VORTAC RWY 32

CATEGORY	A	1	8	С	D	E
S-TAC-32	5000/	50	537	(600-1)	3000/60	37 (600-14)
CIRCLING *	3 300-1	037	(900.1)	3.000.1a	10.00	A100 2
7 (-			(M1.004)	(1100-2)	[1700.2]

VOR-A

CATEGORY	A	В	 T D
CIRCLING *	5300-1	4 837 (900-1%)	5500-2 1037 (1100-2)

NDB RWY 32

CATEGORY	Α	8	С	D	
S-32	5300/50 837 (900-1)	N	NOT AUTHORIZED		
CIRCLING *	5300-1 837 (900-1)	٨	NOT AUTHORIZED		

SID MINIMUMS

TACAN Saturn North/South		600 - 1
Saturn VOR/NDB	0	900 - 1
TACAN Crator North/South		600 - 1
Saturn VOR		900 - 1 1/2

ATTACHMENT 1 TO SOP 50-3105-3